

TABLE OF CONTENTS

GENERAL PROBLEMS OF ELECTROMECHANICS

- Getcha V.Ya., Zakharenko A.B. (JSC «VNIEM Corporation»)**
NEW TECHNICAL SOLUTIONS FOR HIGH-SPEED ENERGY-EFFICIENT ELECTRIC GENERATOR CREATION.....3
Based on usage of modern active materials of stators and rotors cores, constructive materials of rotating elements there were proposed new technical solutions, form and design of high-speed energy-efficient turbo-electric generator. The peculiarity of the turbo-electric generator is a coaxial double-rotor system where each rotor is based on two mounting bearers. As a result the overall length system decreases, its rigidity grows, proper frequencies increase.
Key words: turbocharger system, high-speed turbo-electric generator, rotor system, nanocrystalline alloy.

SPACE ELECTROMECHANICS. SPACECRAFT

- Avksentev A.A., Gorbunin V.I., Zozulya L.P., Chernyavsky V.A. (Military space academy n.a. A.F. Mozhaysky)**
Evdokimov R.A. (JSC «RKK «Energy» after S.P. Korolyov»)
OPTIMIZATION OF SPACECRAFT LEADING OUT SCHEME LIMITED IN SELECTION OF ENGINE UNIT TURN-ON INTERVALS.....7
An approximate numeric analytic method for optimization of ascent trajectory of SC to the preset cell of the ballistic structure is presented. The mission assigning differs from the traditional one in the fact that the engine firing is not always possible, but only in certain allowable sites of the orbit when the SC is able to manoeuvre at certain actual status of its power supply system. The method rests on minor segments trajectory discretization, for which many possible directions of thrust vector of SC in current orbit plane is specified. At that the analytic expressions are used to calculate parameter values increment of the orbit, that enables to formulate an optimization task of the flight trajectory as a search of compromise direction of the thrust vector for each its point at specified characteristics of the engine.
Key words: spacecraft, leading out scheme, microthrust, orbit discretization.

- Belenky A.D., Vasilyev V.N., Semenov A.S., Semenov M.E. (JSC «VNIEM Corporation»)**
«METEOR-M» № 2 SPACECRAFT EARTH SEARCH MODE.....13
Problems of earth search organization after spacecraft separation from the carrier are under consideration. An algorithm for calculation of quaternion of mismatch in response to vertical earth infra-red sensor signals is developed. Control law parameters are calculated. The earth search time is estimated with the aid of a closed system orientation mathematical model at different initial angular positions of the spacecraft.
Key words: spacecraft, attitude control system, attitude mode, quaternion, earth vertical reference, kinematic momentum.

- Vvedensky N.Yu., Pustobaev M.V. (JSC «VNIEM Corporation»)**
ANALYSIS OF SPACE HARDWARE DEVELOPMENT TESTS FOR MECHANICAL EFFECTS IN USA, EC, AND RF.....19
The article presents an analysis of normative documents and practice of leading foreign institutes of the USA (US Department of Defense, NASA) and EC (ESA) in the field of experimental tests of space hardware for mechanical effects. Foreign and national experiences in development tests have been compared, substantial differences in terminology and test methodologies were revealed. Actively applied abroad alternative approaches to reliability testing enabling to lower expenditures for development testing by way of combination of qualification and acceptance tests are described herein.
Key words: spacecraft, normative documents, design performed test, design development tests, preliminary tests, acceptance tests, alternative strategies, protoflight.

- Solovyov A.M. (JSC «Russian space systems»)**
RESULTS OF THEORETIC AND EXPERIMENTAL RESEARCHES AT DEVELOPMENT OF MULTISPECTRAL SCANNER «ROSS-1» FOR WATER SURFACES OBSERVATION.....27
To research a nature of the World ocean and main climate forming factors, a new scientific apparatus (upgraded color scanner) designed for biological and environmental monitoring of seas and oceans, researches of physics processes in their superficial layer is developed. The peculiarity of the under development device is that the useful information obtained with its help is formed by means of quasi simultaneous lateral and longitudinal scanning. In future this will enable to raise an informativeness of the data to be received and accuracy of atmospheric correction at processing this data. The present article represents main results obtained in the course of theoretic and experimental researches of the developed scanner.
Key words: color scanner, aquatory observation, atmospheric correction.

PRODUCTS AND EQUIPMENT TEST PROCEDURES

- Kanunnikova E.A., Krasova N.A., Meshchikhin I.A. (JSC «VNIEM Corporation»)**
IMPACT PULSES GENERATION AS PER PRESET RESPONSE SPECTRA FOR EQUIPMENT TESTING.....33
The article deals with consideration on development of stand test methods of the equipment and apparatus for confirmation of impact loadings. Problems of generation, performance, and test control modes in the form of impact pulses respective to assigned spectrum response are detailed.
Key words: impact pulses, stand tests, apparatus impact loading effects sturdiness, test mode generation.

ELECTROMECHANICS AND SOCIOECONOMIC DEVELOPMENT OF THE COUNTRY

- Bezrodnikh I.P. (SRI RAS)**
Tyutnev A.P., Semenov V.T. (JSC «VNIEM Corporation»)
THE NEAREST SUPERNOVA REMNANTS – PROBABLE HIGH-ENERGY NEUTRONS SOURCES.....39
Nowadays we have sufficient reasons to consider, that remnants of supernova stars are the sources of high-energy particles of galactic cosmic rays. The article draws attention to high level flux intensities of positrons of galactic cosmic rays. Neutrons and positrons are generally products of the same processes of interaction of galactic cosmic rays protons with matters and electromagnetic radiation in residues of supernova and interstellar medium. This serves as an assumption that the particles incorporated in galactic cosmic rays are high-energy neutrons. The energy of neutrons which they must have so that their voyage till the disintegration exceeds a distance from remnants of supernova star to the solar system has been evaluated.
Key words: neutron voyage, high energies, interstellar medium, galactic cosmic rays, Supernova star remnants.

- Korolyov P.V., Kryukov A.P., Puzina Yu.Yu. (FGBOU VPO «NIU MEI»)**
STRUCTURE OF EXPERIMENTAL CELL FOR RESEARCH OF HELIUM-II BOILING IN WEIGHTLESSNESS CONDITIONS.....43
Problems of design of experimental cell for research helium-II film boiling in conditions of microgravity are analyzed. A variant using porous shell of woven metal mat for retention of superfluid liquid volume near the heater at microgravity carried out, for example, during space flight is under consideration. A prototype sample model of the experimental cell for ground testing is described.
Key words: helium-II, heat and mass transfer, two-phase system, boundary surface movement, porous structure.

- Gribanov V.M., Slobodchikov S.S., Potapenko A.I., Ulyaninkov R.V. (FBU «12nd Central scientific research institute of Ministry of Defence»)**
CALCULATION EXPERIMENTAL METHOD FOR DETERMINING ENERGY CONSUMPTION FOR PHYSICAL-CHEMICAL TRANSFORMATIONS IN POLYMER MATERIALS.....51
A method of calculation of energy consumption for physical-chemical transformations in polymer materials based on thermochemistry is represented herein. Using oblique experimental data on phenolic-formaldehyde resins carbonization, a thermal effect of physical-chemical transformations in them was calculated. The resin fractional conversion at assigned polymerization degree is determined.
Key words: polymer, physical-chemical transformations, enthalpy, reaction heat, reagent, reaction products, standard enthalpy of formation.